SlipDoctors®
LEADERS IN FLOOR SAFETY

PRO STRIPE

TECHNICAL DATA SHEET

SlipDoctors® **PRO STRIPE** is a waterborne acrylic paint that is formulated for use on asphalt, concrete, unsealed tile, and more. It is the perfect solution for athletic courts, crosswalks, driveways, parking lots, ramps, and as traffic paint. Our commercial-grade coating is easy to apply and offers a durable, non-textured coating and long-lasting durability.

Special Features
- Interior and Exterior Use
- Barefoot Friendly
- Easy to Apply
- UV & Chemical Resistant
- Fast & Easy Application

Suggested Uses
- Commercial & Residential
- Warehouse Floors
- Traffic Paint & Line Markings
- Sidewalks, Pavers & Stairs
- Parking Lots & Asphalt
- Athletic Courts, Driveways & Ramps



Product Characteristics and Benefits

Surfaces	Concrete, asphalt, metal/steel, pavers, athletic courts, and many other common hard surfaces.
Color	White
Container Size	Gallon (3.78 L) (Quarts & 5-Gallon Pails available as special order)
Product Type	Waterborne Acrylic – Matte Finish
Coverage	Appx 300 sq ft per Gallon, depending on porosity of substrate
Mode of Application	3/8” Nap Roller or Squeegee (not included)
Application Temperature	Surface, air, and product temperature above 50°F (10°C), relative humidity less than 80%. Do not apply if precipitation is expected within 24 hours of application.
Recoat Time	1-2 Hours; Applying 2-3 coats is recommended.
Dry Time	1-2 Hours @ 77°F (25°C)
Water Resistant	Yes
Stain Resistant	Yes
Storage	Protect from freezing. Store locked up in a well-ventilated area. Keep the container tightly closed.
Shelf Life	2 years/original unopened container; 1 year/original opened container
Warranty	2 Years
Removal	Xylene, Paint Thinner or High-Pressure Power Wash
Disposal	Dispose of the container and unused contents in accordance with local, state, and federal regulations.

Precautions & Technical Support

Please refer to Safety Data Sheet (SDS) for detailed Precautions and First Aid Instructions. Pro Stripe Safety Data Sheet can be found at www.slipdoctors.com

Technical Support:
Please contact SlipDoctors at support@slipdoctors.com

SlipDoctors®
LEADERS IN FLOOR SAFETY

PRO STRIPE

TECHNICAL DATA SHEET

Directions for Preparation, Application and Use

Read entire product label, Technical Data Sheet (TDS) & Safety Data Sheet (SDS) before using.

Safety Precautions	• Use in a well-ventilated area. • If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Hotline at 1-800-424-LEAD or www.epa.gov/lead for more information.
Optional Safety Equipment	• Chemical-resistant gloves • Eye Protection • Mask
Surface Preparation	• Surface preparation varies by surface. Please see the chart below for specific instructions for your surface type.

SURFACE TYPE	SURFACE PREPARATION
All Surfaces	Care should be taken to ensure that the surface is clean, dry and free of loose material. A simple leaf blower is typically sufficient to remove gravel and dust in most instances. Areas with oil buildup or existing epoxy coatings may require power washing or abrading the surface before application. **PRO STRIPE** should not be applied on surfaces less than 50°F (10°C), when the relative humidity is greater than 80%, and/or less than 24 hours before expected precipitation.
Painted Surfaces	When applying over previously coated areas, take special care to remove any loose or peeling paint.
Sealed Surfaces	Use caution when painting over freshly sealed surfaces. Sealers can affect adhesion and cure times.
Concrete & Asphalt	New concrete and asphalt should be aged for a minimum of 60 days prior to painting. Moisture barriers are highly recommended. Please test the product for proper adhesion. Consider using SlipDoctors® Prime Coat Resurfacer or SlipDoctors® Water-based Primer. Water Barrier Membrane may also be considered.

Application Instructions

1. Avoid evening and night applications when possible due to cooler temperatures. At lower temperatures or higher humidity, a significant amount of extra time will be required for the paint to dry. Do not apply when temperature and humidity are near or below the dew point.
2. Use a drill mixer or hand stir to thoroughly mix PRO STRIPE before application. No thinning is required.
3. Apply using a 3/8” nap roller. For best results, apply in uniform coats with light even pressure. Avoid thick coats. Wait 1-2 hours to apply second coat. The second coat should be applied at a right angle to the first coat.

Clean Up: Clean spills, splatters, tools, and other equipment promptly with warm soapy water.
Maintenance: Clean with pH-neutral cleaner and low-pressure rinse.

Warranty & Disclaimer

WARRANTY: All properly installed SlipDoctors products are guaranteed to increase the coefficient of friction of your surface for two (2) years (provided surface preparation and cleaning procedures are followed and no contaminants are present). If at any time during the warranty period the treated surface should lose its coefficient of friction, SlipDoctors shall at its option replace any product that proves defective. This warranty applies only to the product itself. Neither the Seller nor the Manufacturer shall be liable for any injury, loss or damage direct or consequential, arising out of the use or the inability to use the product. Before using, Buyer shall determine the suitability of the product for the intended use, and the Buyer assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by Seller and Buyer. Buyer assumes all risks and responsibility associated with disposal. SlipDoctors cannot eliminate all possibilities of slip-and-fall accidents. Please visit www.slipdoctors.com to find further warranty information. KEEP OUT OF REACH OF CHILDREN.