

SAFETY DATA SHEET

BASE COAT

SAFETY DATA SHEET
SLIPDOCTORS BASE COAT – PART A

1. Product and Company Information

Product Code: S-CT-BASELTGRY1G
Product Name: BASE COAT PART A GALLON
Trade Name: SLIPDOCTORS BASE COAT – PART A
Company Name: SlipDoctors
2101 Midway Road, Suite 350
Carrollton, TX 75006 U.S.A.
Emergencies Involving Spills, Leaks
Fires, Exposures, or Accidents
Emergency Contact: CHEMTREC: (800) 424-9300

Phone Number:
(972) 999-9998

2. Hazards Identification

Target Organ Systemic Toxicity (repeated exposure), Category 2
Skin Sensitization, Category 1
Serious Eye Damage/Eye Irritation, Category 2A
Flammable Liquids, Category 3
Acute Toxicity: Skin, Category 4
Acute Toxicity: Inhalation, Category 4
Skin Corrosion/Irritation, Category 3
Aquatic Toxicity (Acute), Category 1



GHS Signal Word: **Danger**

GHS Hazard Phrases:
H226 - Flammable liquid and vapor.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.
H373 - May cause damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects.

GHS Precaution Phrases:
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241 - Use explosion-proof electrical/ventilating/lighting/equipment.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases:
P301+330+331 – IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical aid.
P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+313 - If skin irritation occurs, get medical advice/attention.
P337+313 - If eye irritation persists, get medical advice/attention.
P370+378 - In case of fire, use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.

GHS Storage and Disposal Phrases:
P403+235 - Store in cool/well-ventilated place. Store locked up.
P501 - Contact a licensed professional waste disposal service to dispose of this material.

Potential Health Effects (Acute and Chronic): Chronic inhalation may cause effects similar to those of acute inhalation.

Inhalation: May be harmful if inhaled. Causes respiratory tract irritation. Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. Vapors may cause dizziness or suffocation.

Skin Contact: May be harmful if absorbed through the skin. Causes skin irritation. Prolonged and/or repeated contact may cause irritation and/or dermatitis. Causes redness and pain.

Eye Contact: Causes severe eye irritation. Causes redness andpain.

Ingestion: May be harmful if swallowed. May be harmful if inhaled. Causes respiratory tract irritation. May cause irritation of the digestive tract. May cause gastrointestinal irritationwith nausea, vomiting and diarrhea. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure. Aspiration of material into the lungs may causechemical pneumonitis, which may be fatal.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
14808-60-7	Silicon Dioxide	40.0 - 50.0%
25068-38-6	Epoxy Resin	20.0 - 30.0%
1330-20-7	Xylene (mixed isomers)	10.0 - 20.0%
13463-67-7	Titanium Dioxide	5.0 - 15.0%
84852-15-3	Phenol, 4-nonyl-, branched	1.0 - 5.0%
100-41-4	Ethylbenzene	0.1 - 3.0%
108-65-6	Propylene glycol methyl ether acetate	1.0 - 2.0%

4. First Aid Measures

Emergency and First Aid Procedures

In Case of Inhalation: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Remove from exposure and move to fresh air immediately. Get medical aid.

In Case of Skin Contact: Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If skin irritation occurs, get medical advice/attention.

In Case of Eye Contact: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.

In Case of Ingestion: Never give anything by mouth to an unconscious person. Rinse mouth with water. Do NOT induce vomiting. Get medical aid.

Signs and Symptoms of Exposure: Central nervous system depression. Dermatitis. Abdominal pain, Nausea. Vomiting, Anorexia. Shortness of breath.

Note to Physician: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Treat symptomatically and supportively.

5. Fire Fighting Measures

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam. For large fires apply water from as far away as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

Fire Fighting Instructions: Use water spray to cool unopened containers. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Specific Hazard(s): Flammable Liquid. Emits toxic fumes under fire conditions. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. Flammable liquid and vapor. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas.

Flammable Properties and Hazards: Vapor may travel considerable distance to source of ignition and flash back. Container explosion may occur under fire conditions. Forms explosive mixtures in air.

SLIPDOCTORS BASE COAT – PART A / PAGE 3

6. Accidental Release Measures

Steps To Be Taken In Case Material is Released Or Spilled:
Personal precautions.
Use personal protective equipment.
Spills/Leaks: Control runoff and isolate discharged material for proper disposal. Use water spray to cool and disperse vapors and protect personnel.

7. Handling and Storage

Precautions To Be Taken In Handling:
Avoid contact with skin and eyes. Normal measures for preventive fire protection.
Avoid inhalation of vapor or mist.
Keep away from sources of ignition - No smoking. Take measures to prevent the build-up of electrostatic charge.

Precautions to be Taken In Storing:
Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA
14808-60-7	Silicon Dioxide	PEL: 8825 ppm /(%Si02+5)	TLV: 0.05 MG/M3 (R)
25068-38-6	Epoxy Resin	N/E	N/E
1330-20-7	Xylene (mixed isomers)	PEL: 100 ppm	TLV: 100 ppm STEL: 150 ppm
13463-67-7	Titanium Dioxide	PEL: 15 (dust) mg/m3	TLV: 10 mg/m3
84852-15-3	Phenol, 4-nonyl-, branched	N/A	N/A
100-41-4	Ethylbenzene	PEL: 100 ppm	TLV: 100 ppm STEL: 125 ppm
108-65-6	Propylene Glycol Methyl Ether Acetate	N/E	N/E

Respiratory Equipment:
For higher level protection use type OV/AG/P99 (US) or type ABEK-P2 (EU EN 143) (Specify Type): respirator cartridges. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a back-up to engineering controls.

Eye Protection:
Safety glasses with side shield. For a higher degree of protection, wear chemical splash goggles.

Protective Gloves:
Wear appropriate protective gloves to prevent skin exposure, such as butyl rubber or nitrile rubber.

Other Protective Clothing:
Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation, etc.):
Facilities storing or utilizing this material should be equipped with an eyewash facility and safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Work/Hygienic/ Maintenance Practices:
Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Wash thoroughly after handling. Wash contaminated clothing before reuse.

9. Physical and Chemical Properties

Physical States: [ ] Gas [X] Liquid [ ] Solid
Flash Point: 80°F
Boiling Point: 280°F
Explosive Limits: LEL: 1.0 UEL: 7.1
Weight Per Gallon: 14.2 +/- 1.0
Vapor Pressure (mm Hg): 5.1 @ 68°F
Vapor Density: Heavier than Air
Evaporation Rate: Slower than Ether
Percent Volatile: 18 (Vol) ± 3

10. Stability and Reactivity

Stability: Unstable [ ] Stable [X]

Conditions to Avoid-Instability: Heat, flames and sparks. Ignition sources.

Incompatibility – Materials To Avoid: Strong oxidizing agents, acids

Hazardous Decomposition Or Byproducts: Nature of decomposition products unknown.

Possibility of Hazardous Reactions: Will occur [ ] Will not occur [X]

Conditions To Avoid – Hazardous Reactions: No data available

11. Toxicological Information

Toxicological Information: Germ cell mutagenicity. Reproductive toxicity - no data available.
Aspiration hazard. Inhalation: May cause damage to organs through prolonged or repeated exposure.
Epidemiology: Teratogenicity: No information available.

Carcinogenicity/Other Information: These products contain more than 0.1% crystalline silica (CAS #14808-60-7) which has been classified by IARC a Class 1 carcinogen. Normal application procedures pose no hazard since the silica is set and encapsulated, but grinding or sanding dried films may yield respirable silica dusts. Control exposures to less than 0.1 mg per cubic meter of air using approved dust filter respirators. Skin contact: Prolonged or repeated contact with product may cause slight skin irritation. Impervious gloves should be worn if prolonged skin contact is likely.

ACGIH Carcinogens

Quartz (CAS 14808-60-7)	A2 Suspected human carcinogen
IARC Monographs, Overall Evaluation of Carcinogenicity	1 Carcinogenic to humans
Quartz (CAS 14808-60-7)	1 Carcinogenic to humans
US NTP Report on Carcinogens: Known Carcinogen	
Quartz (CAS 14808-60-7)	Known to be human carcinogen

OSHA PEL: Exposure to airborne crystalline silica shall not exceed an 8 hour time weighted average limit as stated in 29CFR 1910.1000, Table-Z-1-A Air contaminants, specifically: Silica, Crystalline Quartz (Respirable) 0.1 MG/M3. ACGIH TLV-TWA: 01 MG/M3. NIOSH Maximum permissible conc. 0.05 MG/M3, 10 hour workday, 40 hour week. ⚠ This product contains the following substances known to the State of California to cause cancer, birth defects, or other reproductive hazards: Benzene, Toluene, Crystalline Silica.

12. Ecological Information

General Ecological Information: No data available
Persistence and Degradability: No data available
Bioaccumulative Potential: No data available
Mobility in Soil: No data available

13. Disposal Considerations

Waste Disposal Method: Dispose of as unused product. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is flammable. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.

14. Transport Information

LAND TRANSPORT (US DOT): Limited Quantity - Used for 1 gallon containers when shipped in the United States of America.
DOT Proper Shipping Name: UN1263, Paint Related Material, 3, PG III – 5 Gallon pails



Marine Transport IMDG Shipping: UN1263, Paint Related Material, 3, PG III
The marine pollutant mark is not required when transported in sizes of <5 L or <5 kg (per container)



AIR TRANSPORT (ICAO/IATA): UN1263, Paint Related Material, 3, PG III
IATA Shipping Name:



15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986.) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
14808-60-7	Silicon Dioxide	No	No	No
25068-38-6	Epoxy Resin	No	No	No
1330-20-7	Xylene (mixed isomers)	No	Yes 100 LB	Yes
13463-67-7	Titanium dioxide	No	No	No
84852-15-3	Phenol, 4-nonyl-, branched	No	No	No
100-41-4	Ethylbenzene	No	Yes 1000 LB	Yes
108-65-6	Propylene glycol methyl ether acetate	No	No	No

All components in this product are listed in the TSCA Inventory List.

V.O.C. (WHITE) 1.34 LBS/GAL. (161 GMS/L)

16. Other Information

Revision Date: 4/20/2026
Additional Information About This Product:

Hazardous Material Information System III (U.S.A)

Health: 2*
Flammability: 3
Reactivity: 0
Personal Protection: *

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Gulf Coast Paint Mfg., Inc. and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

SAFETY DATA SHEET
SLIPDOCTORS BASE COAT HARDENER – PART B

1. Product and Company Identification

Product Code: S-CT-BASEBQTREG
Product Name: BASE COAT HARDENER PART B QUART
Trade Name: SLIPDOCTORS BASE COAT HARDENER – PART B
Company Name: SlipDoctors
2101 Midway Road, Suite 350
Carrollton, TX 75006 U.S.A.
Emergencies Involving Spills, Leaks
Fires, Exposures, or Accidents
Emergency Contact: CHEMTREC: (800) 424-9300

Phone Number:
(972) 999-9998

2. Hazards Identification

Skin Corrosion/Irritation, Category 1B
Skin Sensitization, Category 1
Serious Eye Damage/Eye Irritation, Category 1
Germ Cell Mutagenicity – Category 2
Acute Toxicity: Oral, Category 4
Aquatic Toxicity (Acute), Category 1
Aquatic Toxicity (Chronic), Category 1



GHS Signal Word **Danger**

GHS Hazard Phrases:
H302 – Harmful if swallowed.
H314 - Causes severe skin burns and eye damage.
H361 – Suspected of damaging fertility or the unborn child.
H411 – Toxic to aquatic life with long lasting effects.

GHS Precaution Phrases:
P202 – Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P264 - Wash hands thoroughly after handling.
P270 – Do not eat, drink or smoke when using this product.
P273 – Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P281 – Use personal protective equipment as required.

GHS Response Phrases:
P301+330+331 – IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical aid.
P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+313 – If skin irritation occurs, get medical advice/attention.
P337+313 - If eye irritation persists, get medical advice/attention.
P370+378 - In case of fire, use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.

GHS Storage and Disposal Phrases:
P501 – Contact a licensed professional waste disposal service to dispose of this material.
P403+235 – Store in a cool/well-ventilated place. Store locked up.

Potential Health Effects (Acute and Chronic):
Chronic inhalation may cause effects similar to those of acute inhalation.

Inhalation:
May be harmful if inhaled. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract.

Skin Contact: May be harmful if absorbed through the skin. Causes skin burns.
Eye Contact: Causes eye burns.
Ingestion: May be harmful if swallowed.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
Proprietary	Epoxy Amine Resin	55.0 - 60.0 %
84852-15-3	Phenol, 4-nonyl-branched	40.0 - 45.0 %

4. First Aid Measures

Emergency and First Aid Procedures:

In Case of Inhalation: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Remove from exposure and move to fresh air immediately. Get medical aid.

In Case of Skin Contact: Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If skin irritation occurs, get medical advice/attention.

In Case of Eye Contact: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.

In Case of Ingestion: Never give anything by mouth to an unconscious person. Rinse mouth with water. Do NOT induce vomiting. Get medical aid.

Note to Physician: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Treat symptomatically and supportively.

5. Fire Fighting Measures

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

Fire Fighting Instructions: Use water spray to cool unopened containers. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Specific Hazard(s): Flammable Liquid. Emits toxic fumes under fire conditions. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. Flammable liquid and vapor. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas. This liquid floats on water and may travel to a source of ignition and spread fire. May accumulate static electricity.

Flammable Properties and Hazards: Vapor may travel considerable distance to source of ignition and flash back. Container explosion may occur under fire conditions. Forms explosive mixtures in air. Wear self- contained breathing apparatus for firefighting, if necessary.

6. Accidental Release Measures

Steps To Be Taken In Case Material is Released or Spilled: Personal precautions.
Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Environmental precautions. Do not let product enter drains. Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

7. Handling and Storage

Precautions To Be Taken in Handling: Avoid inhalation of vapor mist. Normal measures for preventive fire protection.

Precautions To Be Taken In Storing: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA
84852-15-3	Phenol, 4-nonyl-, branched	N/E	N/E
Proprietary	Epoxy Amine Resin	N/E	N/E

Respiratory Equipment (Specify Type):	For nuisance exposures use type P95 (US) or type P1 (EU EN 143) particle respirator. For higher level protection use type OV/AG/P99 (US) or type ABEK-P2 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.
Eye Protection:	Safety glasses with side shield. For a higher degree of protection, wear chemical splash goggles.
Protective Gloves:	Wear appropriate protective gloves to prevent skin exposure, such as butyl rubber or nitrile rubber. Wear appropriate protective clothing to prevent skin exposure.
Other Protective Clothing:	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.
Engineering Controls (Ventilation, etc.)	
Work/Hygienic/Maintenance Practices:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Wash thoroughly after handling. Wash contaminated clothing before reuse.

9. Physical and Chemical Properties

Physical States:	[ ] Gas [X] Liquid [ ] Solid
Flash Point:	>250°F
Boiling Point:	N/A
Explosive Limits:	LEL: N/A UEL: N/A
Weight Per Gallon:	7.90 ± .3
Vapor Pressure (mm Hg):	N/A
Vapor Density:	N/A
Evaporation Rate:	N/A
Percent Volatile:	0

10. Stability and Reactivity

Stability:	Unstable [ ] Stable [X] No data available.
Conditions to Avoid - Instability:	No data available
Incompatibility – Materials To Avoid:	Strong oxidizing agents, acids.
Hazardous Decomposition Or Byproducts:	Nature of decomposition products unknown.
Possibility of Hazardous Reactions:	Will occur [ ] Will not occur [X]
Conditions to Avoid - Hazardous Reactions:	No data available

11. Toxicological Information

Toxicological Information:	
Irritation or Corrosion:	Causes severe skin burns and eye damage.
Carcinogenicity/Other Information:	Carcinogenicity IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH. NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

12. Ecological Information

Bioaccumulative Potential:	No data available.
Mobility in Soil:	No data available
	Toxic to aquatic life with long lasting effects

SLIPDOCTORS BASE COAT HARDENER – PART B / PAGE 4

13. Disposal Considerations

Waste Disposal Method: Dispose of as unused product. This material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.

14. Transport Information

LAND TRANSPORT (US DOT): Limited Quantity – Used for 1 gallon containers and quart cans when shipped in the United States of America.
DOT Proper Shipping Name: UN3066, Paint Related Material, 8, PG III (sizes larger than 1 gallon)



IMDG Shipping Name: UN3066, Paint Related Material, 8, PG III
The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤ 5 kg (per container)



AIR TRANSPORT (ICAO/IATA):
IATA Shipping Name: UN3066, Paint Related Material, 8, PG III



15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
Proprietary	Epoxy Amine Resin	No	No	No
84852-15-3	Phenol, 4-nonyl-, branched	No	No	No

All components in this product are listed in the TSCA Inventory List.

V.O.C. (mixed): 1.34 LBS/GL (161 GMS/L) White

16. Other Information

Revision Date: 4/20/2026
Additional Information About this Product:

Hazardous Material Information System III (U.S.A)

Health: 3
Flammability: 1
Reactivity: 0
Personal Protection: *

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Gulf Coast Paint Mfg., Inc. and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.



SAFETY DATA SHEET

TOP COAT

SAFETY DATA SHEET
SLIPDOCTORS HIGH GLOSS TOPCOAT – PART A

1. Product and Company Information

Product Code: S-CT-TOPCLR1G
Product Name: TOPCOAT PART A BASE GAL CLEAR
Trade Name: SLIPDOCTORS HIGH GLOSS TOPCOAT – PART A
Company Name: SlipDoctors
2101 Midway Road, Suite 350
Carrollton, TX 75006 U.S.A.
Emergencies Involving Spills, Leaks
Fires, Exposures, or Accidents
Emergency Contact: CHEMTREC: (800) 424-9300

Phone Number:
(972) 999-9998

2. Hazards Identification

Flammable Liquids, Category 3
Target Organ Systemic Toxicity (single exposure), Category 3
Toxic To Reproduction, Category 1B
Aquatic Toxicity (Acute), Category 3



GHS Signal Word: **Danger**

GHS Hazard Phrases:
H226 - Flammable liquid and vapor.
H302 – Harmful if swallowed.
H315 – Causes skin irritation.
H319 – Causes serious eye irritation.
H332 – Harmful if inhaled.
H360 - May damage fertility or the unborn child.
H402 - Harmful to aquatic life.

GHS Precaution Phrases:
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241 - Use explosion-proof electrical/ventilating/lighting/ equipment.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases:
P301+330+331 – IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical aid.
303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+313 - If skin irritation occurs, get medical advice/attention.
P337+313 - If eye irritation persists, get medical advice/attention.
P370+378 - In case of fire, use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.

GHS Storage and Disposal Phrases:
P403+235 - Store in cool/well-ventilated place. Store locked up.
P501-Contact a licensed professional waste disposal service to dispose of this material.

Potential Health Effects (Acute and Chronic):
Chronic inhalation may cause effects similar to those of acute inhalation.

Inhalation:
Material is irritating to mucous membranes and upper respiratory tract. Harmful if inhaled. Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. Vapors may cause dizziness or suffocation.

Skin Contact:
May be harmful if absorbed through the skin. Prolonged and/or repeated contact may cause irritation and/or dermatitis.

Eye Contact: Causes eye irritation. Causes redness and pain.

Ingestion: May be harmful if swallowed. May be harmful if inhaled. May cause irritation of the digestive tract. May cause gastrointestinal irritation with nausea, vomiting and diarrhea. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
Proprietary	Polyester poly-urethane	50.0 – 60.0%
123-86-4	Butyl acetate	38.0 – 48.0%
108-65-6	Propylene glycol methyl ether acetate	1.0 – 5.0%

4. First Aid Measures

In Case of Inhalation: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Remove from exposure and move to fresh air immediately. Get medical aid.

In Case of Skin Contact: Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If skin irritation occurs, get medical advice/attention.

In Case of Eye Contact: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.

In Case of Ingestion: Never give anything by mouth to an unconscious person. Rinse mouth with water. Do NOT induce vomiting. Get medical aid.

Note to Physician: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Treat symptomatically and supportively.

5. Fire Fighting Measures

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

Fire Fighting Instructions: Use water spray to cool unopened containers. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Flammable Properties and Hazards: Specific Hazard(s): Flammable Liquid. Emits toxic fumes under fire conditions. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. Flammable liquid and vapor. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas. Vapor may travel considerable distance to source of ignition and flash back. Container explosion may occur under fire conditions. Forms explosive mixtures in air.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled: Personal precautions.
Use personal protective equipment.
Spills/Leaks: Control runoff and isolate discharged material for proper disposal. Use water spray to cool and disperse vapors and protect personnel.

7. Handling and Storage

Precautions To Be Taken in Handling: Avoid contact with skin and eyes. Normal measures for preventive fire protection. Avoid inhalation of vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.

Precautions To Be Taken in Storing: Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep away from heat, sparks, and open flame.

SLIPDOCTORS HIGH GLOSS TOPCOAT – PART A / PAGE 3

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA
Proprietary	Polyester poly-urethane	N/E	N/E
123-86-4	Butyl acetate	PEL: 150 ppm	TLV: 150 ppm STEL: 200 ppm
108-65-6	Propylene glycol methyl ether acetate	N/E	N/E

Respiratory Equipment: (Specify Type): For higher level protection use type OV/AG/P99 (US) or type ABEK-P2 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.

Eye Protection: Safety glasses with side shield. For a higher degree of protection, wear chemical splash goggles.

Protective Gloves: Wear appropriate protective gloves to prevent skin exposure, such as butyl rubber or nitrile rubber.

Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls: (Ventilation, etc.) Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Work/Hygienic/Maintenance Practices: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Wash thoroughly after handling. Wash contaminated clothing before reuse.

9. Physical and Chemical Properties

Physical States: [ ] Gas [X] Liquid [ ] Solid

Flash Point: 81°F

Boiling Point: 252°F

Explosive Limits: LEL: 1.7 UEL: 7.5

Weight Per Gallon: 8.5 +/- .25

Vapor Pressure (mm Hg): 8.4 @ 68°F

Vapor Density: Heavier than Air

Evaporation Rate: Slower than Ether

Percent Volatile: 52 (Vol)

10. Reactivity and Stability

Stability: Unstable [ ] Stable [X]

Conditions To Avoid – Instability: Heat, flames and sparks

Incompatibility - Materials To Avoid: Bases. Strong oxidizing agents.

Hazardous Decomposition Or Byproducts: Nature of decomposition unknown.

Possibility of Hazardous Reactions: Will occur [ ] Will not occur [X]

11. Toxicological Information

Toxicological Information: No information found.

Carcinogenicity/Other Information: IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

12. Ecological Information

General Ecological Information: No data available
Persistence and Degradability: No data available
Bioaccumulative Potential: No data available
Mobility in Soil: No data available

13. Disposal Considerations

Waste Disposal Method: Dispose of as unused product. This material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material. Dispose of any unused product.

14. Transport Information

LAND TRANSPORT (US DOT): Limited Quantity – Used for 1 gallon containers when shipped in the United States of America
DOT Proper Shipping Name: UN1263, Paint Related Material, 3, PG III – 5 Gallon pails



Marine Transport
IMDG Shipping: UN1263, Paint Related Material, 3, PG III



AIR TRANSPORT (ICAO/IATA)
IATA Shipping Name: UN1263, Paint Related Material, 3, PG III



15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
Proprietary	Polyester poly-urethane	No	No	No
123-86-4	Butyl acetate	No	Yes 5000 lb	No
108-65-6	Propylene glycol methyl ether acetate	No	No	No

All components in this product are listed in the TSCA Inventory List.

V.O.C. MIXED: 3.25 LBS/GL (389 GMS/L)

16. Other Information

Revision Date: 1/5/2026
Additional Information About This Product:

Hazardous Material Information System III (U.S.A)

Health: 2
Flammability: 3
Reactivity: 0
Personal Protection: *

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by SlipDoctors and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

SAFETY DATA SHEET
SLIPDOCTORS HIGH GLOSS TOPCOAT – PART B

1. Product and Company Identification

Product Code: S-CT-TOPBQTREG
Product Name: TOPCOAT PART B HARDENER 0.5 GAL
Trade Name: SLIPDOCTORS HIGH GLOSS TOPCOAT – PART B
Company Name: SlipDoctors
2101 Midway Road, Suite 350
Carrollton, TX 75006 U.S.A.
Emergencies Involving Spills, Leaks
Fires, Exposures, or Accidents
Emergency Contact: CHEMTREC: (800) 424-9300

Phone Number:
(972) 999-9998

2. Hazards Identification

Serious Eye Damage/Eye Irritation, Category 2A
Respiratory Sensitization, Category 1
Flammable Liquids, Category 3
Target Organ Systemic Toxicity (single exposure), Category 3
Acute Toxicity: Skin, Category 4
Skin Corrosion/Irritation, Category 2
Acute Toxicity: Inhalation, Category 4



GHS Signal Word: **Danger**

GHS Hazard Phrases:
H226 - Flammable liquid and vapor.
H312 - Harmful in contact with skin.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 - May cause respiratory irritation.

GHS Precaution Phrases:
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 - Keep container tightly closed.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.
P260 – Do not breathe dust/fume/gas/mist/vapors/spray.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P285 - In case of inadequate ventilation wear respiratory protection.

GHS Response Phrases:
P301+330+331 – IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical aid.
P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+313 - If skin irritation occurs, get medical advice/attention.
P337+313 - If eye irritation persists, get medical advice/attention.
P370+378 - In case of fire, use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.

GHS Storage and Disposal Phrases:
P403+235 - Store in cool/well-ventilated place. Store locked up.
P501-Contact a licensed professional waste disposal service to dispose of this material.

Potential Health Effects (Acute and Chronic): Chronic inhalation may cause effects similar to those of acute inhalation.

Inhalation: Material is irritating to mucous membranes and upper respiratory tract. Harmful if inhaled. Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. Vapors may cause dizziness or suffocation.

Skin Contact: May be harmful if absorbed through the skin. Prolonged and/or repeated contact may cause irritation and/or dermatitis.

Eye Contact: Causes eye irritation. Causes redness and pain.

Ingestion: May be harmful if swallowed. May be harmful if inhaled. May cause irritation of the digestive tract. May cause gastrointestinal irritation with nausea, vomiting and diarrhea. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
28182-81-2	Poly(hexamethylene diisocyanate)	70.0 – 80.0%
123-86-4	Butyl acetate	10.0 – 20.0%
1330-20-7	Xylene (mixed isomers)	10.0 – 20.0%
100-41-4	Ethylbenzene	0.1 – 4.0%

4. First Aid Measures

Emergency and First Aid Procedures:

In Case of Inhalation: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Remove from exposure and move to fresh air immediately. Get medical aid.

In Case of Skin Contact: Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If skin irritation occurs, get medical advice/attention.

In Case of Eye Contact: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.

In Case of Ingestion: Never give anything by mouth to an unconscious person. Rinse mouth with water. Do NOT induce vomiting.

Note to Physician: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Treat symptomatically and supportively.

5. Fire Fighting Measures

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water of water. Use water spray, dry chemical, carbon dioxide, or appropriate foam.

Fire Fighting Instructions: Use water spray to cool unopened containers. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Specific Hazard(s): Flammable Liquid: Emits toxic fumes under fire conditions. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. Flammable liquid and vapor. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas.

Flammable Properties and Hazards: Vapor may travel considerable distance to source of ignition and flash back. Container explosion may occur under fire conditions. Forms explosive mixtures in air.

6. Accidental Release Measures

Steps To Be Taken In Case Material is Released or Spilled: Personal precautions.
Use personal protective equipment.
Spills/Leaks: Control runoff and isolate discharged material for proper disposal. Use water spray to cool and disperse vapors and protect personnel.

7. Handling and Storage

Precautions to be Taken in Handling: Avoid contact with skin and eyes. Normal measures for preventive fire protection. Avoid inhalation of vapor or mist.
Keep away from sources of ignition - No smoking. Take measures to prevent the build-up of electrostatic charge.

Precautions to be Taken in Storing: Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep away from heat, sparks, and open flame.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA
28182-81-2	Poly(hexamethylene diisocyanate)	N/A	N/A
123-86-4	Butyl acetate	PEL: 150 ppm	TLV: 150 ppm STEL: 200 ppm
1330-20-7	Xylene (mixed isomers)	PEL: 100 ppm	TLV: 100 ppm STEL: 150 ppm
100-41-4	Ethylbenzene	PEL: 100 ppm	TLV: 100 ppm STEL: 125 ppm

Respiratory Equipment (Specify Type): For higher level protection use type OV/AG/P99 (US) or type ABEK-P2 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.

Eye Protection: Safety glasses with side shield. For a higher degree of protection, wear chemical splash goggles.

Protective Gloves: Wear appropriate protective gloves to prevent skin exposure, such as butyl rubber or nitrile rubber.

Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation, etc.) Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Work/Hygienic/Maintenance Practices: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Wash thoroughly after handling. Wash contaminated clothing before reuse.

9. Physical and Chemical Properties

Physical States: [ ] Gas [X] Liquid [ ] Solid

Flash Point: 80°F

Boiling Point: 300°F

Explosive Limits: LEL: 1.0 UEL: 7.5

Weight Per Gallon: 8.8 ± .25

Vapor Pressure (mm Hg): 8.4 @ 68°F

Vapor Density: Heavier than Air

Evaporation Rate: Slower than Ether

Percent Volatile: 30

10. Stability and Reactivity

Stability: Unstable [ ] Stable [X]

Conditions to Avoid - Instability: Heat, flames and sparks:

Incompatibility – Materials To Avoid: Bases, Strong oxidizing agents.

Hazardous Decomposition Or Byproducts: Nature of decomposition products unknown.

Possibility of Hazardous Reactions: Will occur [ ] Will not occur [X]

11. Toxicological Information

Toxicological Information: Other information on acute toxicity. No data available.
Respiratory or skin sensitization: Germ cell mutagenicity. Reproductive toxicity - no data available.
Teratogenicity: No data available.
Specific target organ toxicity -single exposure (Globally Harmonized System) Specific target organ toxicity – repeated exposure (Globally Harmonized System)
Aspiration hazard. Epidemiology: No information found.
Teratogenicity: Exposure to n-butyl acetate vapors throughout gestation did not cause significant teratogenicity in rabbits, rats, or mice.
Reproductive Effects: Mutagenicity: Neurotoxicity: Other Studies: Acute toxicity. No data available.

Irritation or Corrosion: Serious eye damage/eye irritation:

Sensitization: No data available.

Chronic Toxicological Effects: No data available.
Carcinogenicity/Other Information: Carcinogenicity.
IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. ⚠ This product contains the following substances known to the State of California to cause cancer, birth defects, or other reproductive hazards: Benzene, Toluene.

12. Ecological Information

General Ecological Information: No data available
Persistence and Degradability: No data available
Bioaccumulative Potential: No data available
Mobility in Soil: No data available

13. Disposal Considerations

Waste Disposal Method: Dispose of as unused product. This material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material. Dispose of any unused product.

14. Transport Information

LAND TRANSPORT (US DOT): Limited Quantity – Used for 1 gallon containers when shipped in the United States of America
DOT Proper Shipping Name: UN1263, Paint Related Material, 3, PG III – 5 Gallon pails



Marine Transport
IMDG Shipping: UN1263, Paint Related Material, 3, PG III



AIR TRANSPORT (ICAO/IATA)
IATA Shipping Name: UN1263, Paint Related Material, 3, PG III



15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
Proprietary	Polyester poly-urethane	No	No	No
123-86-4	Butyl acetate	No	Yes 5000 lb	No
108-65-6	Propylene glycol methyl ether acetate	No	No	No

All components in this product are listed in the TSCA Inventory List.

V.O.C. MIXED: 3.25 LBS/GL (389 GMS/L)

16. Other Information

Revision Date: 1/5/2026
Additional Information About This Product:

Hazardous Material Information System III (U.S.A)

Health: 2
Flammability: 3
Reactivity: 0
Personal Protection: *

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by SlipDoctors and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.



SAFETY DATA SHEET

FLAKES

SAFETY DATA SHEET

1. IDENTIFICATION

Product:	EPOXY FLOOR PAINT FLAKES FOR GARAGES & WAREHOUSES
Manufacturer:	SLIPDOCTORS
Address:	2101 MIDWAY ROAD, SUITE 350 CARROLLTON, TX 75006 USA
Phone:	(972) 999-9998
Email:	support@slipdoctors.com
Website:	www.slipdoctors.com
Emergency:	Chemtrec / (800) 424-9300 (US and Canada) or consult a physician

2. HAZARDS IDENTIFICATION

This product is considered non-hazardous under the OSHA Hazard Communication Standard (29CFR1910.120).

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	CAS Number	Composition
Barium Sulfate	7727-43-7	35 – 45 %
Calcium Carbonate	471-34-1	35 – 45 %
Proprietary Resins	N/E	10 – 20%
Titanium Dioxide	13463-67-7	0 – 10%
Pigment(s)	N/A	< 3 %

4. FIRST-AID MEASURES

Skin

Wash off with soap and water. If symptoms persist, call a physician.

Eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.

Inhalation

Move to fresh air. If symptoms persist, call a physician.

Ingestion

If swallowed, seek medical advice immediately. If conscious, drink plenty of water. Do not induce vomiting without medical advice.

5. FIRE-FIGHTING MEASURES

This product is not known to present any fire hazard.

6. ACCIDENTAL RELEASE MEASURES

Sweep, shovel and/or vacuum to clean up spillage. Deposit into covered container for disposal. All material should be disposed of in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Handling

No special safety measures required.

Storage

Store material in an air tight poly-bag in a dry environment at room temperature to avoid moisture, humidity and product degradation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Eye Protection:	Safety glasses recommended.
Skin Protection:	Use appropriate protective clothing.
Hand Protection:	Protective leather, cloth or rubber gloves recommended.
Respiratory Protection:	Use of dust respirator recommended when exposure limits may be exceeded.
Ventilation:	Local exhaust ventilation to collector or containment recommended.
Hygiene Measures:	Good industrial hygiene practices required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point:	N/A	**Specific Gravity (H_2O = 1):**	1.6 – 3.1
Vapor Density:	Not Volatile	**Appearance:**	Miscellaneous Colors
Coating V.O.C.:	Not Volatile	**Odor:**	Odorless
Material V.O.C.:	Not Volatile	**Melting Point:**	N/A
Solubility in Water:	Insoluble	**Evaporation Rate:**	N/A

10. STABILITY AND REACTIVITY

Stability:	Stable, but will react violently with sulfuric acid or alkali materials.
Incompatibility:	None
Hazardous Byproducts:	None

11. TOXICOLOGICAL INFORMATION

Chronic Toxicity

This product is not listed as a carcinogen by the IARC, NTP or OSHA.
According to the current knowledge this product is harmless. Therefore, no health damaging effects are expected if safety measures are followed. No specific testing has been done on this product.

12. ECOLOGICAL INFORMATION

No ecological testing has been done on this product.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with local, state and federal regulations.

14. TRANSPORT INFORMATION

Not Regulated: Ship as Class 55

15. REGULATORY INFORMATION

U.S. Toxic Substances Control Act:	Compliant with regulations.
Sara Title III – Sections 312 & 313:	Not hazardous.
California Proposition 65:	No ingredients in this product are known to cause cancer, birth defects or reproductive hazards.
Canadian Domestic Substances List:	All ingredients in this product are listed or exempt from listing.

16. OTHER INFORMATION

Disclaimer

The information contained herein is based on the data available to us and is believed to be correct. SlipDoctors makes no warranty expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. SlipDoctors assumes no responsibility for injury, loss or damage from the use of the product described.

N/A = Not Applicable N/D = Not Determined N/E = Not Established



SAFETY DATA SHEET

EXTRA GRIP

Safety Data Sheet

Date of Preparation: 3/9/06

Revision: 1/18/26

Section 1 - Chemical Product and Company Identification

Product: EXTRA GRIP CLEAR ANTI-SLIP ADDITIVE
Chemical Family: Poly Allyl DiGlycol Carbonate **Recommended use:** various

SlipDoctors
2101 Midway Road, Suite 350
Carrollton, TX 75006
Phone: (972) 999-9998, Fax: (214) 666-3225

Emergency Phone: (800) 424-9300
Date Revised: 1/18/18

Section 2 - Hazards Identification

Classification of the chemical in accordance with paragraph (d) of 1910.122: combustible dust
Signal Word: Warning
Symbol: None
Hazard Statements: May form combustible dust concentrations in air.
Precautionary Statements: None
Hazards not otherwise classified: None

Section 3 - Composition / Information on Ingredients

Ingredient Name	CAS Number	Percent by Weight
Poly Allyl DiGlycol Carbonate	25656-90-0	>99.5%
Anti-static agent	002764-13-8	<0.5%

Section 4 - First Aid Measures

Description of necessary measures, subdivided according to the different routes of exposure:
Inhalation: If overcome by high dust concentrations, remove to a ventilated area. Call physician if irritation persists.
Eye Contact: Flush eyes thoroughly for 15 minutes taking care to rinse under eyelids. Do not scrub. Abrasion may cause irritation. If discomfort continues, continue to wash with water. If irritation persists, consult a physician.
Skin Contact: Wash skin thoroughly with soap and water. Consult a physician if irritation persists.
Ingestion: If swallowed, give large amounts of water, induce vomiting. Consult a physician.

Most important symptoms and effects, acute and delayed:
Inhalation: Potential respiratory tract irritation.
Eye Contact: Exposure to eyes from solids or dusts may cause irritation or scratch the surface of the eye.
Skin Contact: Potential of slight irritation to the skin.
Ingestion: May be harmful if swallowed.

Indication of immediate medical attention and special treatment needed: Treat symptomatically.

Section 5 - Fire-Fighting Measures

Suitable Extinguishing Media: Foam, Water spray, carbon dioxide, or other dry chemical.
Unsuitable Extinguishing Media: None.

Specific hazards arising from the chemical:
Unusual Fire or Explosion Hazards: Dust can form explosive mixture with air. Sealed (closed) containers can build up pressure if exposed to heat (fire).
Hazardous Combustion Products: Smoke, propane, carbon dioxide.
Sensitivity to Static Discharge: Avoid generating dust. Fine dust dispersed in air, in sufficient concentrations, and in the present of an ignition source is a potential dust explosion hazard.
Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face-piece operated in pressure-demand or positive-pressure mode. Wear full protective clothing.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment, and emergency procedures: Wear safety glasses with side shields, gloves, and dust mask.

Methods and materials for containment and cleaning up: Sweep up and place in appropriate disposal container. Avoid generating dust or accumulating dust. Avoid dust dispersal in the air. Spilled material can be a slipping hazard. Eliminate flames, sparks, excessive temperatures, and oxidizing agents. Non-sparking tools should be used.

Section 7 - Handling and Storage

Precautions for safe handling: Avoid contact with eyes and skin. Use in a well-ventilated area. Avoid generation and breathing of dust. Minimize dust generation and accumulation.

Storage Requirements: Store in closed, properly labeled containers in a cool, ventilated area. Keep away from heat, open flames, and oxidizing agents. Do not transfer to unmarked containers.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls:

Ventilation: Mechanical ventilation and local exhaust. Use explosion proof electrical equipment for very high dust levels. Ensure ventilation and dust-handling systems prevent the escape of dust into work areas and that there is no leakage from the equipment.

Administrative Controls:

Respiratory Protection: Recommend a 3M #8710 or equivalent dust mask.

Protective Clothing/Equipment: Use rubber gloves. Wash thoroughly before eating, smoking, applying cosmetics, etc. Safety glasses with side shield, goggles and/or a face shield. If necessary, protective rubber apron, shoes, or boots, or TYVEC protective suit with hood.

Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

	OSHA PEL		ACGIH TLV	
Ingredient	**TWA**	**STEL**	**TWA**	**STEL**
Poly Allyl DiGlycol Carbonate	none estab.	none estab.	none estab.	none estab.
Anti-static agent	none estab.	none estab.	none estab.	none estab.

Section 9 - Physical and Chemical Properties

Appearance: granular clear solid
Odor: odorless
Odor Threshold: n/e
pH: 5.19
Freezing/Melting Point: not applicable
Boiling Point: not applicable
Flash Point: not applicable
Flash Point Method: not applicable
Evaporation Rate: not applicable
Flammability Classification: Non-flammable.
Upper/lower flammability or explosive limits: not applicable

Vapor Pressure: not applicable
Vapor Density (Air=1): not applicable
Relative Density: 1.31
Water Solubility: Insoluble
Other Solubilities: not determined
Partition coefficient: n-octanol/water; not determined
Auto-ignition Temperature: Not determined.
Decomposition Temperature: Not determined
Viscosity: not applicable

Section 10 - Stability and Reactivity

Reactivity: Not reactive under normal conditions.

Chemical Stability: This product is stable at room temperature in closed containers under normal storage and handling conditions.

Possibility of Hazardous Reactions: None under normal processing. Hazardous polymerization does not occur.

Conditions to Avoid: Excessive heat, ignition sources.

Incompatible materials: Oxidizing agents.

Hazardous Decomposition Products: Smoke, propane, carbon dioxide.

Section 11- Toxicological Information

Information on the likely routes of exposure:

Inhalation: Inhalation of high concentrations of this inert nuisance particulate can result in mild irritation of the respiratory tract.

Eye: May cause irritation or scratch the surface of the eye through mechanical abrasion.

Skin: May cause slight irritation.

Ingestion: May be harmful if swallowed.

Symptoms related to the physical, chemical, and toxicological characteristics:

Eye: Exposure to eyes from solids or dusts may cause irritation or scratch the surface of the eye.

Skin: Potential of slight irritation to skin.

Ingestion: May be harmful if swallowed.

Inhalation: Potential respiratory tract irritation if inhaled.

Delayed and immediate effects as well as chronic effects from short- and long-term exposure: Irritation of eyes, skin.

Numerical measures of toxicity: Not determined.

Carcinogenicity: NTP, IARC, or OSHA does not consider this product carcinogenic.

Section 12 - Ecological Information

Ecotoxicity: This product is not classified as environmentally hazardous.

Persistence and degradability: Not determined.

Bioaccumulative potential: Not determined.

Mobility in soil: Not determined.

Section 13 - Disposal Considerations

Disposal: Dispose as solid waste and contaminated packaging in sanitary landfill or incinerate according to Federal, State, and local regulations.

Section 14 - Transport Information

DOT Transportation Data (49 CFR 172.101): This product is not classified as dangerous under the transport regulations for road, rail, sea, or air transport.

NMF classification: Class 60-Item 156200

UN Number: None

UN proper shipping name: None

Transport hazard classes: DOT-not regulated; IATA-not regulated; IMDG-not regulated

Packing group: None

Environmental hazard: No

Transport in bulk according to Annex II or MARPOL 73/78 and the IBC Code: not regulated

Special precautions: None

Section 15 - Regulatory Information

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

RCRA Hazardous Waste Classification: Not classified

CERCLA Hazardous Substance (40 CFR 302.4) Not listed

SARA Toxic Chemical (40 CFR 372.65): Not listed

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed

OSHA Regulations:

Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): Not listed

TSCA

This substance is on the Chemical Substances Inventory of the Toxic Substance Control Act (TSCA Inventory [USA]). Please note that this product is not subject to any legal reporting requirements under these acts.

International Regulations:

Australia: Present on AICS.

Canada: Present on Non-Domestic Substances List (NDSL).

China: Not present.

Europe: Not present on EINECS.

Japan: Present on ENCS. 6-1159

Korea: Present on ECL. KE-10464

New Zealand: Not present.

Philippines: Not present on PICCS.

revision_date 1/18/26

Section 16 - Other Information

Prepared By: Stephanie Nichols
Revision Notes: updated section 2, added Ultra 325

Product Grades Available from the R. J. Marshall Company (this list may be incomplete):

Ultra 4	Ultra 8	Ultra 12	Ultra 16	Ultra 20
Ultra 40	Ultra 60	Ultra 100	Ultra 200	Ultra 300
Ultra 325	Ultra 1200	Ultra -30	Ultra 16RM	Ultra 20RM
Ultra 35AA	Ultra -3/8			

Disclaimer: Information contained herein is presented in good faith and is based on data believed to be accurate. However no warranty is expressed or implied regarding this information or the results obtained from the use of this Safety Data Sheet, whether it originates with SlipDoctors or others. This Safety Data Sheet relates only to the specific material designated herein. It does not relate to use with other material or processes. This information is supplied with the condition that the user will make appropriate determination as to its suitability for their purpose prior to using it.