SlipDoctors®
LEADERS IN FLOOR SAFETY

BONDING AGENT

TECHNICAL DATA SHEET

CLICK TO LEARN MORE →

SlipDoctors Bonding Agent is exclusively designed to maximize the bond of coatings and paints on those hard-to-coat substrates. Can be used in oil-modified urethanes, waterborne urethanes, moisture-cure urethanes, acid-cure coatings, UV curable coatings, epoxies, acrylic sealers, stains and paints.

Special Features
- Does not alter color/sheen of coating
- Oil and Water compatible
- Does not alter traction of grit-based coatings
- Increases life and function of coatings
- Reduces bonding and adhesion problems

Suggested Uses
- Metal surfaces
- Marble and Granite surfaces
- High polished porcelain
- Terrazzo
- Composite Decking
- Concrete
- Surfaces that are hard, smooth, polished and/or glossy



Product Characteristics and Benefits

Surfaces	Dependent upon base coating choice.
Color	Clear liquid additive
Mode of Application	Pre-mix into base coat prior to application (2 ounces Bonding Agent per gallon of coating product).
Container Size	2 oz and 8 oz bottles
Dry Time	Follow base coat recommendations. This product is generally used in first- coat application only. Will not increase or decrease dry times.
Water Resistant	N/A
Stain Resistant	N/A
Product Type	Carbon Silicon base bonding adhesion promoter.
Coverage	Dependent upon base coating rates.
Storage	Store tightly sealed at room temperature. Do not freeze. Once mixed, use within 48 hours.
Shelf Life	N/A
Warranty	2 years
Removal	If spilled, wipe off and clean surface with soapy water and rinse.
Disposal	Dispose of container and unused contents in accordance with local, state and federal regulations.

Precautions & Technical Support

Please refer to Safety Data Sheet (SDS) for detailed Precautions and First Aid Instructions.
Bonding Agent Safety Data Sheet can be found at www.slipdoctors.com

Technical Support:
Please contact SlipDoctors at support@slipdoctors.com

SlipDoctors®
LEADERS IN FLOOR SAFETY

BONDING AGENT

TECHNICAL DATA SHEET

Directions for Preparation, Application and Use

Read entire product label, Technical Data Sheet (TDS) and Safety Data Sheet (SDS) before using.



Safety Precautions	• Avoid contact with eyes and inhalation of vapors. • Immediately wash off product with soap and water if it comes in contact with skin. • Use product in a well-ventilated area. • Keep away from heat, sparks and flames. • If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Hotline at 1-800-424-LEAD or www.epa.gov/lead.
Optional Safety Equipment	• Chemical-resistant gloves • Clothing to cover all skin areas • Eye protection
Surface Preparation	Follow coating manufacturer's instructions for surface prep. Use surface preparations listed for the base coating product by the manufacturer.
Application Instructions	**Step 1:** Remove cap and pour slowly. Mix well into the coating product. Let product set for 5 minutes. Use 2 ounces of bonding agent for every gallon of product. **Step 2:** Pour product into application tray and apply according to base coat manufacturer's recommendations. **Step 3:** Save leftover mixed product and re-stir before using on second coat if applied within 48 hours of original mixing.
Maintenance	Follow base coat manufacturer's instructions.

Warranty & Disclaimer

WARRANTY: All properly installed SlipDoctors products are guaranteed to increase the coefficient of friction of your surface for two (2) years (provided surface preparation and cleaning procedures are followed and no contaminants are present). If at any time during the warranty period the treated surface should lose its coefficient of friction, SlipDoctors shall at its option replace any product that proves defective. This warranty applies only to the product itself. Neither the Seller nor the Manufacturer shall be liable for any injury, loss or damage direct or consequential, arising out of the use or the inability to use the product. Before using, Buyer shall determine the suitability of the product for the intended use, and the Buyer assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by Seller and Buyer. Buyer assumes all risks and responsibility associated with disposal. SlipDoctors cannot eliminate all possibilities of slip-and-fall accidents. Please visit www.slipdoctors.com to find further warranty information. KEEP OUT OF REACH OF CHILDREN.