SlipDoctors®
LEADERS IN FLOOR SAFETY

EXTRA GRIP CLEAR

TECHNICAL DATA SHEET

CLICK TO LEARN MORE →

SlipDoctors® EXTRA GRIP CLEAR Slip-Resistant Additive is a micronized polymer additive that can be used with both solvent-based and water-based coatings and paints to create an anti-slip surface and increase traction to help prevent slips and falls. Ideal for use with clear coatings. Our exclusive clear additive will not change the color or any other properties of your coating product.

Special Features
- Interior and Exterior Use
- Increases Traction
- Durable Anti-Slip Finish
- Easy to Use
- Barefoot Friendly
- Paw Friendly
- Chemical Resistant

Suggested Uses
- Patios
- Garage Floors
- Driveways
- Walkways
- Steps & Stairs
- Ramps
- Residential & Commercial



Product Characteristics and Benefits

Surfaces	Compatible with clear and color paints and coatings. Use with Acrylic, Latex, Urethane, Epoxy and other oil- and water-based color coatings.
Color	Clear
Container Size	4 oz (113 gr) / 20 oz (566 gr)
Product Type	Micronized Polymer
Coverage	Add up to 4 oz (113 gr) per gallon of coating
Mode of Application	Follow coating manufacturer's instructions.
Dry Time	Follow coating manufacturer's instructions.
Water Resistant	Yes
Storage	Store unused Extra Grip Clear tightly sealed in a cool dry place away from humidity. Unused mixed product can be stored according to coating manufacturer's instructions.
Shelf Life	5 years
Warranty	N/A
Removal	Follow coating manufacturer's instructions for removal.
Disposal	Dispose of container and unused contents in accordance with local, state, and federal regulations.

Precautions & Technical Support

Please refer to Safety Data Sheet (SDS) for detailed Precautions and First Aid Instructions. Extra Grip Clear Safety Data Sheet can be found at www.slipdoctors.com

Technical Support:
Please contact SlipDoctors at support@slipdoctors.com

SlipDoctors®
LEADERS IN FLOOR SAFETY

EXTRA GRIP CLEAR

TECHNICAL DATA SHEET



Directions for Preparation, Application and Use

Read entire product label, Technical Data Sheet (TDS) & Safety Data Sheet (SDS) before using.

Surface Preparation	Follow the coating or paint manufacturer's instructions for surface preparation.
Application Instructions	1. Mix up to 4 oz (113 gr) of Extra Grip Clear with coating in a separate container. 2. Mix thoroughly into paint until an even and consistent mixture is achieved. 3. Apply using a 3/8" to 3/4" nap roller following coating manufacturer's application instructions. Stir occasionally to ensure that particles are well distributed throughout mixture. 4. When applying two coats, Extra Grip can be used in both coats. 5. Follow coating manufacturer's instructions for dry times and clean up.

Warranty & Disclaimer

WARRANTY: All properly installed SlipDoctors products are guaranteed to increase the coefficient of friction of your surface for two (2) years (provided surface preparation and cleaning procedures are followed and no contaminants are present). If at any time during the warranty period the treated surface should lose its coefficient of friction, SlipDoctors shall at its option replace any product that proves defective. This warranty applies only to the product itself. Neither the Seller nor the Manufacturer shall be liable for any injury, loss or damage direct or consequential, arising out of the use or the inability to use the product. Before using, Buyer shall determine the suitability of the product for the intended use, and the Buyer assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by Seller and Buyer. Buyer assumes all risks and responsibility associated with disposal. SlipDoctors cannot eliminate all possibilities of slip-and-fall accidents. Please visit www.slipdoctors.com to find further warranty information. KEEP OUT OF REACH OF CHILDREN.