SlipDoctors®
LEADERS IN FLOOR SAFETY

EXTRA GRIP

TECHNICAL DATA SHEET

CLICK TO LEARN MORE →

SlipDoctors Extra Grip Additive is a non-skid paint additive that can be easily added to most floor paints and coatings to provide better grip and increase traction on indoor and outdoor surfaces. Extra Grip creates a safe, skid-resistant finish while retaining the color, coverage and performance of your coating. Compatible with most epoxy, urethane, and acrylic coatings, both water- and solvent-based. NOT RECOMMENDED FOR USE IN CLEAR COATINGS.

Special Features
- Interior and Exterior Use
- Increases Traction
- Durable Anti-Slip Finish
- Easy to Use
- Barefoot Friendly
- Paw Friendly
- Chemical Resistant

Suggested Uses
- Patios
- Garage Floors
- Driveways
- Walkways
- Steps & Stairs
- Ramps
- Residential & Commercial



Product Characteristics and Benefits

Surfaces	Compatible with color paints and coatings. Use with Acrylic, Latex, Urethane, Epoxy and other oil- and water-based color coatings.
Color	Light Gray
Container Size	12 oz (340 gr) / 60 oz (1700 gr)
Product Type	Ground Pumice
Coverage	Add up to 12 oz (340 gr) per gallon of coating
Mode of Application	Follow coating manufacturer's instructions.
Dry Time	Follow coating manufacturer's instructions.
Water Resistant	Yes
Storage	Store unused Extra Grip tightly sealed in a cool dry place away from humidity. Unused mixed product can be stored according to coating manufacturer's instructions.
Shelf Life	5 years
Warranty	N/A
Removal	Follow coating manufacturer's instructions for removal.
Disposal	Dispose of container and unused contents in accordance with local, state, and federal regulations.

Precautions & Technical Support

Please refer to Safety Data Sheet (SDS) for detailed Precautions and First Aid Instructions. Extra Grip Safety Data Sheet can be found at www.slipdoctors.com

Technical Support:
Please contact SlipDoctors at support@slipdoctors.com

SlipDoctors®
LEADERS IN FLOOR SAFETY

EXTRA GRIP

TECHNICAL DATA SHEET



Directions for Preparation, Application and Use

Read entire product label, Technical Data Sheet (TDS) & Safety Data Sheet (SDS) before using.

Surface Preparation	Follow the coating or paint manufacturer's instructions for surface preparation.
Application Instructions	1. Mix up to 12 oz (340 gr) of Extra Grip with coating in a separate container. 2. Mix thoroughly into paint until an even and consistent mixture is achieved. 3. Apply using a 3/8" to 3/4" nap roller following coating manufacturer's application instructions. Stir occasionally to ensure that particles are well distributed throughout mixture. 4. When applying two coats, Extra Grip can be used in both coats. 5. Follow coating manufacturer's instructions for dry times and clean up.

Warranty & Disclaimer

WARRANTY: All properly installed SlipDoctors products are guaranteed to increase the coefficient of friction of your surface for two (2) years (provided surface preparation and cleaning procedures are followed and no contaminants are present). If at any time during the warranty period the treated surface should lose its coefficient of friction, SlipDoctors shall at its option replace any product that proves defective. This warranty applies only to the product itself. Neither the Seller nor the Manufacturer shall be liable for any injury, loss or damage direct or consequential, arising out of the use or the inability to use the product. Before using, Buyer shall determine the suitability of the product for the intended use, and the Buyer assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by Seller and Buyer. Buyer assumes all risks and responsibility associated with disposal. SlipDoctors cannot eliminate all possibilities of slip-and-fall accidents. Please visit www.slipdoctors.com to find further warranty information. KEEP OUT OF REACH OF CHILDREN.