SlipDoctors®
LEADERS IN FLOOR SAFETY

GRIP X

TECHNICAL DATA SHEET

CLICK TO LEARN MORE →

SlipDoctors GripX is a durable anti-slip coating specifically formulated to increase the slip resistance on tiles, natural, stamped, and stained concrete, sealed surfaces, and most other natural stone. GripX is an easy-to-apply roll-on coating that once cured has a semi-gloss, barefoot-friendly textured finish and can be used indoors or outdoors. Can be used to seal tiles to help prevent water damage, scuff marks and scratches. This water-based formula offers UV protection that is chemical resistant for maximum durability.

Special Features
- Interior and Exterior Use
- Barefoot Friendly
- Increases Traction
- UV & Chemical Resistant
- Chlorine Resistant
- Non-Yellowing
- Fast & Easy Application

Suggested Uses
- Commercial & Residential
- Stamped, Sealed & Stained Concrete
- Driveways
- Patios
- Swimming Pool Areas
- Concrete & Stone Decks



Product Characteristics and Benefits

Surfaces	Stamped, sealed & stained concrete, tile & natural stone.
Color	Milky-white liquid with grit. Dries to a clear semi-gloss finish.
Container Size	Quart (32 oz / 946 ml)
Product Type	Water-based Acrylic Sealer.
Coverage	Up to 150 sq ft per quart
Mode of Application	3/8” Nap Roller (not included)
Application Temperature	Surface, air, and product temperature above 40°F (4°C) and at least 5°F (2°C) above the dew point.
Recoat Time	2-4 Hours
Dry Time	Light Traffic: 6-12 Hours / Normal Traffic: 24 Hours
Water Resistant	Yes, but cannot be continuously submerged.
Stain Resistant	Yes
Storage	Store in a dry area at ambient room temperature of 72°F (22°C). Do not freeze.
Shelf Life	2 years in original unopened container; 1 year in opened container.
Warranty	2 Years
Removal	Xylene or Paint Thinner
Disposal	Dispose of container and unused contents in accordance with local, state, and federal regulations.

Precautions & Technical Support

Please refer to Safety Data Sheet (SDS) for detailed Precautions and First Aid Instructions. GripX Safety Data Sheet can be found at www.slipdoctors.com

Technical Support:
Please contact SlipDoctors at support@slipdoctors.com

SlipDoctors®
LEADERS IN FLOOR SAFETY

GRIP X

TECHNICAL DATA SHEET

Directions for Preparation, Application and Use	
Read entire product label, Technical Data Sheet (TDS) & Safety Data Sheet (SDS) before using.	
Safety Precautions	• Use in a well-ventilated area. • If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Hotline at 1-800-424-LEAD or www.epa.gov/lead for more information.
Optional Safety Equipment	• Chemical-resistant gloves • Eye protection • Mask
Surface Preparation	Surface preparation varies by surface. Please see chart below for specific instructions for your surface type.



Surface Preparation	
Surface Type	**Surface Preparation**
All Surfaces	All substrates must be clean, dry, and free of dust, dirt, oil, grease, soil, soap residue, wax, flaking paint and other soluble contaminants. Do not use alcohol-based cleaners. For best adhesion, lightly sand surface using 400 grit sandpaper or etch using SlipDoctors® Maintain Grip. Rinse thoroughly and allow to dry completely before application.
Painted Surfaces	GripX cannot be applied over painted surfaces. All paint must be removed before application.
Sealed Surfaces	Chipped or flaking surfaces should be sanded or scuffed to a sound surface. If sealed surface is sound, lightly sand with 400 grit sandpaper or use SlipDoctors® Bonding Agent to promote adhesion. Scrub and clean surface with pH-neutral cleaner. Rinse thoroughly and allow to dry before application.
Uncoated Concrete	New concrete should be allowed to cure for 30 days before application of any coating.
Unsealed Tiles & Natural Stone	Clean surface using pH-neutral cleaner or power wash, rinse and allow to dry thoroughly before application. For best adhesion, etch the surface using SlipDoctors® Stone Grip prior to application.
Wood & Synthetic Surfaces	GripX should not be applied to wood, synthetic or painted surfaces.

SlipDoctors®
LEADERS IN FLOOR SAFETY

GRIP X

TECHNICAL DATA SHEET

Application Instructions	
Application	1. TEST: GripX should be tested on a small inconspicuous area before full application. 2. Pour GripX into a separate container and stir thoroughly to make sure additive is evenly distributed. Stir often during application to ensure consistent distribution. Do not thin. 3. Apply two coats using a 3/8” nap roller. Allow the first coat to dry for 2-4 hours before applying the second coat. The second coat should be applied at a right angle to the first coat. 4. Depending on the porosity of the surface, additional coats can be applied for increased durability and traction. 5. Allow 6 – 12 hours to cure for light traffic and 24 hours to cure for normal traffic.
Cleaning	For best results, clean with a pH-neutral cleaner and scrub lightly with a soft bristle deck brush or use a low-pressure wash. Avoid alcohol-based cleaners.
Removal	GripX can be removed from the surface using xylene, paint stripper or a high-pressure wash. Removal method depends on the substrate.

Warranty & Disclaimer

WARRANTY: All properly installed SlipDoctors products are guaranteed to increase the coefficient of friction of your surface for two (2) years (provided surface preparation and cleaning procedures are followed and no contaminants are present). If at any time during the warranty period the treated surface should lose its coefficient of friction, SlipDoctors shall at its option replace any product that proves defective. This warranty applies only to the product itself. Neither the Seller nor the Manufacturer shall be liable for any injury, loss or damage direct or consequential, arising out of the use or the inability to use the product. Before using, Buyer shall determine the suitability of the product for the intended use, and the Buyer assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by Seller and Buyer. Buyer assumes all risks and responsibility associated with disposal. SlipDoctors cannot eliminate all possibilities of slip-and-fall accidents. Please visit www.slipdoctors.com to find further warranty information. KEEP OUT OF REACH OF CHILDREN.