SlipDoctors®
LEADERS IN FLOOR SAFETY

MAINTAIN GRIP

TECHNICAL DATA SHEET

CLICK TO LEARN MORE →

SlipDoctors Maintain Grip is a specialized cleaner for use on surfaces previously treated with our Stone Grip anti-slip treatment. Maintain Grip is an effective cleaner designed to break down oils, grease and other contaminants on the surface, and effectively removes hardened grease build-up. Maintain Grip works to renew the microscopic treads, providing anti-slip traction to wet and dry surfaces. Maintain Grip can be used for daily cleaning and to remove heavy duty grease build-up in commercial, residential and industrial areas.

Special Features

- Interior & Exterior use
- Breaks Down Oil and Grease
- Fast & Easy Application
- Made for use with Stone Grip
- NFS Certified
- Safe for Use in Food Processing Areas
- Maintains & Renews Traction

Suggested Uses

- Residential, Commercial & Industrial
- Food Processing Establishments
- Restaurants
- Schools
- Hospitals
- Hotels
- Patios, Showers & Restrooms



Product Characteristics and Benefits	
Surfaces	Quarry tile, glazed tile, ceramic tile, porcelain tile and concrete.
Color	N/A
Mode of Application	Mop
Container Size	Gallon
Application Temperature	Above 40°F (4°C) surface temperature; evaporation may occur at higher temperatures.
Dry Times	N/A
Water Resistant	N/A
Stain Resistant	N/A
Product Type	Commercial Strength Cleaner
Coverage	Up to 40,000 sq.ft./gallon after dilution
Storage	Store in dry area at ambient room temperature of 72°F / 22°C
Shelf Life	5 years
Removal	N/A
Disposal	Dispose of container and unused contents in accordance with local, state, and federal regulations.

Precautions & Technical Support

Please refer to Safety Data Sheet (SDS) for detailed Precautions and First Aid Instructions.
Maintain Grip Safety Data Sheet can be found at www.slipdoctors.com

Technical Support:
Please contact SlipDoctors at support@slipdoctors.com

SlipDoctors®
LEADERS IN FLOOR SAFETY

MAINTAIN GRIP

TECHNICAL DATA SHEET



Directions for Preparation, Application and Use

Read entire product label, Technical Data Sheet (TDS) & Safety Data Sheet (SDS) before using.

Safety Precautions	• Keep children and small pets out of area until surface has been thoroughly dried. • Gloves should be worn at all times.
Recommended Safety Equipment	• Chemical-resistant gloves • Closed Toe Shoes • Eye protection
Surface Preparation	Wipe up any spills and sweep debris from floor surface. Since floor tile compositions differ greatly among manufacturers, **ALWAYS** test product on a small, inconspicuous area for acceptance, appearance and results prior to application over the entire area.

Notice: *Do not use on any synthetic surface such as wood, laminate, vinyl, VCT or fiberglass. Not recommended for use on glass, polished marble, granite or terrazzo with marble chips, as it may remove shine from highly polished surfaces. If product gets on aluminum, remove promptly with a clean, wet towel.*

Dilution Ratio and Cleaning Instructions

Surface Type	Dilution	Cleaning Instructions
Normally Soiled Floors	1 oz Maintain Grip to 1 gallon of warm water	Apply diluted solution to floor surface using a wet mop. Aggressively scrub the floor using a deck brush. Do not allow the solution to dry on the surface. Mop up soiled solution or squeegee to drain. Rinse or damp mop floor using clean water. Dry floor using a mop or squeegee.
Concrete & Heavily Soiled Floors	4 oz Maintain Grip to 1 gallon of warm water	Apply diluted solution to floor surface using a wet mop and allow to stand for 3-5 minutes. Aggressively scrub the floor using a deck brush. Do not allow the solution to dry on the surface. Mop up soiled solution or squeegee to drain. Rinse or damp mop floor using clean water. Dry floor using a mop or squeegee.

Warranty & Disclaimer

WARRANTY: All properly installed SlipDoctors products are guaranteed to increase the coefficient of friction of your surface for two (2) years (provided surface preparation and cleaning procedures are followed and no contaminants are present). If at any time during the warranty period the treated surface should lose its coefficient of friction, SlipDoctors shall at its option replace any product that proves defective. This warranty applies only to the product itself. Neither the Seller nor the Manufacturer shall be liable for any injury, loss or damage direct or consequential, arising out of the use or the inability to use the product. Before using, Buyer shall determine the suitability of the product for the intended use, and the Buyer assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by Seller and Buyer. Buyer assumes all risks and responsibility associated with disposal. SlipDoctors cannot eliminate all possibilities of slip-and-fall accidents. Please visit www.slipdoctors.com to find further warranty information. KEEP OUT OF REACH OF CHILDREN.