

Technical Data Sheet

Product Description – SlipDoctors’ Non-Slip Spray is an epoxy aerosol spray that provides a hard, textured finish that helps to prevent slip-and-fall accidents. It is barefoot friendly, lead-free and chemical, gas and oil resistant. Works great on both interior and exterior surfaces, and is ideal for areas where water is present or slippery conditions exist. This convenient aerosol spray is the perfect solution to treat small or irregularly shaped surfaces where increased traction is desired. SlipDoctors’ Non-Slip Spray can be used on fiberglass and acrylic bathtubs and showers, properly prepared wood, concrete, metal, tiles, porcelain/ceramic and many other surfaces.

SlipDoctors Non-Slip Spray

Special Features

- Interior & Exterior use
- Barefoot Friendly
- Increases Traction
- Available in Clear & White
- Self-Priming
- Weather Resistant
- Fast & Easy Application

Suggested Uses

- Fiberglass & Acrylic Bathtubs/showers
- Kitchens & Bathrooms
- Pool Decks, Ladders & Steps
- Boats & Trailers
- Gyms & Spas
- Hotels & Resorts
- Residential & Commercial Use

Product Characteristics and Benefits

| | |
|--------------------------------|--|
| Surfaces | Fiberglass and acrylic bathtubs/showers, properly prepared wood, concrete, metal, tiles and porcelain/ceramic surfaces |
| Color | Clear & White |
| Mode of Application | Aerosol Spray |
| Size | Net Wt. 12.0 oz / 340 g metal aerosol can |
| Application Temperature | 70°F-90°F / 21°C-32°C |
| Dry to Touch | 10 to 20 minutes at 77°F / 25°C |
| Recoat | Approximately 1 hour at 77°F / 25°C |
| Dries Hard | 24 Hours |
| Water Resistant | Yes |
| Stain Resistant | Yes |
| Product Type | Epoxy |
| Coverage | Up to 15 sq.ft./can |
| Storage | Store in dry area at ambient room temperature of 72°F / 22°C |
| Shelf Life | 1 year |
| Warranty | 2 years |
| Removal | Lacquer thinner |
| Disposal | Dispose of container and unused contents in accordance with local, state, and federal regulations. |

Directions for Preparation, Application and Use

Read entire product label, Technical Data Sheet (TDS) and Safety Data Sheet (SDS) before using.

Safety Precautions:

- Non-Slip Spray must be used in a well ventilated area.
- Never use Non-Slip Spray near an open flame.
- If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Hotline at 1-800-424-LEAD or www.epa.gov/lead

Recommended Safety Equipment:

- Chemical-resistant gloves
- Eye protection
- Mask

Surface Preparation: Varies by surface. Please see chart below for preparation for specific surfaces. **ALWAYS:** Test a small area for color compatibility and adhesion. For best results, spray between 70-90°F / 20-32°C. Applying SlipDoctors' Non-Slip Spray below 50°F/10°C will cause the paint to spray and/or dry improperly. Dry time decreases with higher temperatures and increases with lower temperatures. Overspray can be cleaned with paint or lacquer thinner.

Application Instructions:

- Step 1** Surface should be dry, clean and free of oil, wax, dirt, loose paint and other contaminants. If necessary, remove old paint down to the original surface.
- Step 2** Mix contents of can well by shaking until the ball rattles within the can. Once ball rattles, continue to shake vigorously for 2-3 minutes. During use, shake intermittently for 10 seconds to keep product mixed.
- Step 3** Spray 6-12 inches away from surface in a sweeping motion during application. When applying, note that 2-3 light coats will cure, protect and look better than one heavy coat.
- Step 4** If spray stops or is irregular, turn can upside down and spray for 2-3 seconds to clear nozzle. Wipe tip, shake can and resume. **IMPORTANT:** Before storing partial can, clean valve immediately after use. To clean: Hold can upside down and spray until only clear gas comes out (approximately 3 seconds), then wipe tip and store. If spray nozzle becomes clogged, remove and clean in lacquer thinner.

| FLOORING SURFACE | PREPARATION |
|------------------------------------|---|
| FIBERGLASS & ACRYLIC | Sand lightly to promote adhesion. Wash with soap and water or wipe with clean cloth and lacquer thinner (or another cleaner that does not leave a film or residue) to remove all sanding dust. Allow to dry thoroughly. |
| INTERIOR/ EXTERIOR WOOD | INTERIOR: All waxes and polishes must be completely removed from the surface before application. Surfaces must be thoroughly cleaned and prepared by appropriate sanding methods. Using a 220 grit sandpaper is recommended to lightly scuff the floor. Prior to the coating application, remove all dust from floor and surrounding structures. |
| | EXTERIOR: Sand where necessary to remove loose wood grains and splinters. Using a power washer or high pressure hose, clean wood surface thoroughly to remove all dirt, grease or other contaminants. Allow to dry completely before coating (Could take 2-3 days depending on temperature without rain or dew). Please check temperature requirements on previous page. |

| | |
|--|--|
| TILE & PORCELAIN | Surface should be thoroughly cleaned before application. Do not use cleaners that leave a film or residue after cleaning. Allow to dry thoroughly. Test product on tile by spraying on a small area. Wait 24-48 hours, test for adhesion by using duct tape. Press tape down evenly on coating and then remove. If no paint comes up on tape, adhesion is good. If paint comes off, you may need to scuff, sand or etch the tile lightly to promote adhesion. Be sure to remove all dust from tile before application. If applying on a bathtub or tiled shower, it is important to allow at least 24 hours' cure time before resuming normal use. If product will be subject to prolonged periods of soaking in water, allow 48 hours for product to fully cure before use. |
| PAINTED/ UNPAINTED ALUMINUM & METAL | PAINTED ALUMINUM: Surface should be free of grease, rust or loose particles. Clean with soap and water or another cleaner that will not leave a film or residue. Allow the metal surface to dry thoroughly before coating with Spray. Apply SlipDoctors' Non-Slip Spray on a small test area to check for adhesion before full application. Apply directly to aluminum. No primer is needed. UNPAINTED ALUMINUM & METAL: Surface should be free of grease, rust or loose particles. Wipe down surface with etching solution or lacquer thinner. Clean with soap and water or another cleaner that will not leave a film or residue. Allow the metal surface to dry thoroughly before coating with Spray. Apply directly to aluminum. No primer is needed. |
| EXTERIOR CONCRETE | Remove all loose debris using a power washer or high pressure hose. Using an etching solution is recommended to remove all grease, dirt or other contaminants. Rinse concrete thoroughly to remove the etching solution and allow to dry thoroughly (often 1-2 days depending on temperature, rain, dew and humidity). For new pours, allow concrete to season before coating – approximately 60 days. Apply Spray directly to concrete. No primer is needed. |

Precautions & Technical Support

Please refer to **Safety Data Sheet (SDS)** for detailed **Precautions and First Aid Instructions**.

Non-Slip Spray *Clear & White* Safety Data Sheet can be found at www.slipdoctors.com

Technical Support: Please contact SlipDoctors at 1-888-436-5404 or cs@slipdoctors.com

Office Hours: Monday - Friday from 8:00 am - 5:00 pm CST

Warranty & Disclaimer

WARRANTY: All properly installed SlipDoctors products are guaranteed to increase the coefficient of friction of your surface for 2 years (provided surface preparation and cleaning procedures are followed and no contaminants are present). If at any time during the warranty period the treated surface should lose its coefficient of friction, SlipDoctors shall at its option replace any product that proves defective. This warranty applies only to the product itself. Neither the seller nor the manufacturer shall be liable for any injury, loss or damage direct or consequential, arising out of the use or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and the user assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by seller and manufacturer. Buyer assumes all risks and responsibility associated with disposal. SlipDoctors cannot eliminate all possibilities of slip-and-fall accidents. Please visit www.slipdoctors.com to find further warranty information.

KEEP OUT OF REACH OF CHILDREN