

# TUFF GRIP CROSSLINKER

## Urethane Activator

**PRODUCT DESCRIPTION** Tuff Grip Crosslinker Urethane Activator is specifically formulated to be mixed as an activator with SlipDoctors' Tuff Grip. Tuff Grip Crosslinker Urethane Activator is a high-solids, high-viscosity activator designed for conventional use. Mix 1 Pint Tuff Grip Crosslinker Activator per 1 gallon of SlipDoctors' Tuff Grip. Mixed material will have a pot life of 4-6 hours

**RECOMMENDED USES** Substrates include both interior and exterior applications on metal, wood, and masonry as well as O.E.M. farm machinery, feed and grain bins, livestock equipment, structural steel, tanks, trailers, and general industrial finishing where a high-performance paint coating is desired.

**APPLICATION** **Mixing:** Mix 1 pint Tuff Grip Crosslinker activator to 1 gallon of SlipDoctors' Tuff Grip. Mixed material will have a pot life of 4-6 hours.  
**Cleanup:** Clean spills, spatters, hands, tools and other equipment promptly. Give spray equipment a final flush with mineral spirits to help prevent corrosion. Dispose of used paint and waste in accordance with local, state, and federal regulations.  
**Precautions & Limitations:**  
 Do not use Tuff Grip Crosslinker in products containing mineral spirits or VM&P Naphtha!

COLOR:	Clear
VEHICLE TYPE:	Urethane
WEIGHT GALLON:	8.7 ± 0.2 lb./gal.
WEIGHT SOLIDS:	75 ± 2.0 %
VOLUME SOLIDS:	70 ± 2.0 %
VISCOSITY:	1,500 cps @ 77°F
FLASH POINT:	80 °F
VOC (g/l):	260 g/l
GRIND:	#7
HMIS/NFPA:	2,3,0
THINNING & CLEANUP:	MAK or Xylol

**ENVIRONMENTAL & SAFETY STATEMENT:** This product is not formulated with any lead, chrome or mercury containing ingredients. CAUTION! Keep away from heat and open flame. Avoid prolonged contact with skin and breathing of vapor or spray mist. Do not take internally. Close container after each use. Use only with adequate ventilation. Use respiratory devices and other personal protective equipment required by OSHA 29CFR 1910. KEEP OUT OF REACH OF CHILDREN. For specific safety requirements, refer to the Material Safety Data Sheet.

**LIMITATION OF LIABILITY:** To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance, but is subject to change without prior notice. We make no guarantee of any kind, express or implied, including merchantability and fitness for particular purposes. Liability, if any, is limited to replacement of the product or refund of the purchase price. Labor, or cost of labor, and other consequential damages are hereby excluded.